



TD3RCCB

Function: detection and interruption of earth leakage current

Application: protection from electric shock. Must be combined with an upstream device providing appropriate overload and short-circuit protection for the circuit.

Standard: EN 61008-1

Voltage: Un: 240V AC phase-to-neutral, 415V AC phase-to-phase

Residual current breaking capacity: Im = 1500A

Rigid conductor: 25mm² maximum

Flexible conductor: 16mm² maximum



TD3RCBO Residual current circuit breaker with overload protection

Function: detection and interruption of earth leakage current, overloads and short-circuits.

Application: commercial premises. Neutral conductor switched on 2-module versions and unswitched on 1-module versions

Breaking capacity Icn: 6kA (2P), 10kA (1P) to EN 61008-1

Voltage: Un: 240V AC

Rigid conductor: 16mm² maximum (1P), 25mm² maximum (2P)

Flexible conductor: 10mm² maximum (1P), 16mm² (2P)

Poles	DIN Modules	In (A) at 30°C	
		30mA	300mA
2P	2	25-63 types AC, A	25-63, type AC
4P	4	25-100 types AC, A	25-100 types AC, A AC-S

DIN Modules	In (A) at 30°C	
	30mA	300mA
1	6-40, types B,C	
2	25-100 types AC, A, AC-S	25-100 types AC, A, AC-S

DIMENSIONS



DIMENSIONS



